



Sturdy design. Easy to assemble. **An affordable solution.**

Designing an ergonomic workplace with **upCentric™ height adjustable tables** increases employee productivity, allowing workers to easily alternate between seated and standing positions throughout the work day to reduce back pain, reduce stress and to improve circulation throughout the body.

The sturdy upCentric open frame design accommodates a variety of different tabletop widths and provides optimal knee clearance, space for storage and minimalist aesthetics to complement any workspace.



upCentric 2-Leg in White



upCentric Modular 2-Leg in Silver



upCentric 3-Leg in Black

## Expandable frame specs

SPECIFICATIONS	2-LEG-SMALL	2-LEG	3-LEG
Height range	21.6"-47.9"	21.6"-47.9"	21.6"-47.9"
Width range	42"-72"	46"-77"	Long side 46"-77"   Short side 42"-72"
Depth of frame	22" (19 ½")	29 ½" (23 ¾")	22" (19 ½")
Assembly time	5-10 minutes	5-10 minutes	25-40 minutes
Travel speed	1.6" per second	1.6" per second	1.6" per second
Digital memory control buttons	4-Position memory	4-Position memory	4-Position memory
Weight capacity	300 lbs	300 lbs	420 lbs
Electric TiMOTION® motors	2 Motors	2 Motors	3 Motors
Max power draw	30 W	30 W	30 W
Standby power draw	0.06 W	0.06 W	0.06 W
Sound level	39 dB	39 dB	39 dB
Accommodates tabletop sizes	24"d x 42"w up to 28"d x 84"w	24"d x 46"w up to 42"d x 96"w	42"d x 48"w up to 84"d x 96"w
Frame finish	White, silver or black	White, silver or black	White, silver or black
Power cord length	78 ¾"	78 ¾"	78 ¾"
Certification	BIFMA G1   BIFMA X5.5   CSA   UL	BIFMA G1   BIFMA X5.5   CSA   UL	BIFMA G1   BIFMA X5.5   CSA   UL

## Modular frame specs

SPECIFICATIONS	MOD-2-LEG-SMALL	MOD-2-LEG
Height range	21.6"-47.9"	21.6"-47.9"
Depth range	19"-28"	28"-36"
Width range	24"-42"	24"-42"
Travel speed	1.6" per second	1.6" per second
Digital memory control buttons	4-Position memory	4-Position memory
Weight capacity	250 lbs	250 lbs
Electric TiMOTION® motors	2 Motors	2 Motors
Max power draw	30 W	30 W
Standby power draw	0.06 W	0.06 W
Sound level	39 dB	39 dB
Frame finish	Silver or black	Silver or black
Power cord length	78 ¾"	78 ¾"
Certification	BIFMA G1   BIFMA X5.5 CSA   UL	BIFMA G1   BIFMA X5.5 CSA   UL

## Options and warranty

### FRAME FINISH OPTIONS



\*White frame not available for modular legs.

### OPTIONS

- Available as frame only or with tabletop
- Enhanced anti-collision sensor
- Casters
- Peg leg (3-leg only)

### WARRANTY

10 Years

- Frame structure and steel components
- High pressure laminate tabletops

5 years

- Motor, wires and electrical components